## **AMENDMENT TO THE CLAIMS**

- 1. (Currently Amended) A racket string correction tool, capable of moving a displaced string and wedge it inusing a notch and/or hook, and cutting ita string to balance the tension of the accidentally cuta string section at an off-centered point, characterized because it has both actuators wherein the notch, hook, and cutting device are combined in a single longitudinal body, said tool comprising a hilt, said hilt comprising a first end provided with an actuating point defined by a gradual reduction in its section, with two lateral faces distally converging as a wedge with a transversal notch to which the string may be forced and a lateral appendage that provides a hook, and a second end, which axially forms a cap whose most outstanding point presents including a notch that houses the cutting edge of a blade, assembled with a depth that exceeds, at least, the string half section.
- 2. (Original) A tool for adjusting placement and tension of racket strings, said tool comprising:
  - a hilt having a first portion and a second portion, wherein the first portion comprises an actuating end including a hook and two lateral faces distally converging as a wedge near the hook; and
  - wherein a second portion includes a blade for cutting a racket string.
- 3. (Original) The tool of claim 2, further comprising grooves formed on the hilt.
- 4. (New) A racket string aligning device having three tools combined in a single longitudinal body;
  - said device comprising a hilt;

said hilt comprising a first end having two lateral faces distally converging to form a wedge with a transverse notch in which a string may be forced and a lateral appendage that provides a hook; and

said hilt further comprising a second end including a notch which houses a cutting edge.

- 5. (New) A tool for aligning racket strings, said tool comprising:
  - a hilt having first and second opposing portions;
  - said first portion comprising a hook and two lateral faces distally converging to form a wedge adjacent to the hook; and

said second portion comprising a blade for cutting the racket string.